

Gripsert Information



Gripsert planks are used the same way as any other type of timber when building ramps, walkways and steps. The following product information and recommendations should be taken into consideration when quoting and ordering:

- Gripsert comes only as a complete system i.e. timber and aluminium together
- Gripsert is currently only available from Rampworx Ltd
- Planks are 140mm x 45mm, kiln-dried, CCA-treated H3.2 pine
- Allow minimum of 5mm between planks when fitting to allow for expansion when wet
- Skew nail using 90mm (minimum) annular grooved flat head stainless steel nails (these are available from Rampworx Ltd at a competitive price)
- Don't use nail guns
- All Gripsert planks must have at least 10mm per metre cross-fall from either the left or right to allow product to self-drain
- When requesting a quote, please advise the length of the planks required and the quantity
- We can cut custom tapered planks if required for a specific situation (additional cost for this)
- We can freight nationwide (not included in price)
- Weight per metre is 3.18kg
- High rating in slip tests means better traction, especially in wet conditions
- Less on-going maintenance required on pedestrian surfaces
- Aluminium tread is designed to improve drainage and reduce risk of icing up
- New Zealand designed and manufactured for prompt service and delivery
- Less mess on site as planks are precut to your specs (although you may need to trim them for custom jobs or to angle for corners or curves)
- AS WE PREPARE GRIPSERT SPECIFICALLY FOR EACH JOB, IF YOU HAVE BEEN SUCCESSFUL WINNING A TENDER OR HAVE SET START/FINISH DATES FOR A JOB PLEASE ADVISE US IMMEDIATELY SO WE CAN SCHEDULE YOUR JOB TO MEET TIME FRAMES. THERE MAY BE SEVERAL WEEKS' LEAD TIME.